

FLOOR STAND DIGITAL SIGNAGE



*The image is for reference only, the actual product shall prevail!

Product Features:

1. 32inch to 65inch available
2. Full HD display, super slim design
3. 3mm tempered glass in front for protection
4. Flexible structure for standalone, android or PC system
5. Support CMS software
6. Wide application for retail signage, shopping malls, hotels, restaurants, etc.

| Items | V032FDS02 | V043FDS02 | V049FDS02 | V055FDS02 | V065FDS02 | V075FDS02 | V086FDS02 |
|-----------------------------------|---|--|------------------------|------------------------|--------------------------|----------------------------|----------------------|
| Display | | | | | | | |
| Panel Size | 32inch | 43inch | 49/50inch | 55inch | 65inch | 75inch | 86inch |
| Active Area | 697.6845mm(W)×392.256mm(H) | 940.24mm(W)×533.26mm(H) | 1073.6mm(W)×604.4mm(H) | 1209.6mm(W)×680.4mm(H) | 1428.48(H) × 803.52(V)mm | 1649.66 × 927.936 mm (H×V) | 1872(W) × 1053(H) mm |
| Aspect Ratio | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 |
| Contrast Ratio | 4000:1 | 4000:1 | 4000:1 | 4000:1 | 4000:1 | 4000:1 | 4000:1 |
| View angle | 178°(H/V) | 178°(H/V) | 178°(H/V) | 178°(H/V) | 178°(H/V) | 178°(H/V) | 178°(H/V) |
| Brightness | 300nits | 350nits | 350nits | 350nits | 350nits | 400nits | 450nits |
| Resolution | 1920*1080 | 1366*768 | 1920*1080 | 1920*1080 | 1920*1080 | 3840*2160 | 3840*2160 |
| Panel Life | 50000hours | 50000hours | 50000hours | 50000hours | 50000hours | 50000hours | 50000hours |
| Support Color | 16.7M | 16.7M | 16.7M | 16.7M | 16.7M | 16.7M | 16.7M |
| Response Time | 5ms | 8ms | 8ms | 8ms | 8ms | 8ms | 8ms |
| Touch parameter (optional) | | | | | | | |
| Touch technology | IR Touch/ PCAP Touch | | | | | | |
| Touch type | 10-point high precision | | | | | | |
| Touch resolution | 32768*32768/ 4096*4096 | | | | | | |
| Touch accuracy | ±2mm (more than 90% touch area) | | | | | | |
| Touch Tool | finger,touch pen,soft pen or finger with gloves | | | | | | |
| Response Time | <6ms | | | | | | |
| Writing Height | <2mm | | | | | | |
| Operating system | Windows/Linux/Mac/Android/Chrome | | | | | | |
| Android system options | | | | | | | |
| Android option 1 | CPU | RK3288 , quad core, main frequency 1.8GHz | | | | | |
| | RAM+ROM | Standard configuration 2G+8G, optional with 2+16G,4+32G,4+64G; | | | | | |
| | Android system | Android 7.1/Android 10 | | | | | |
| Android option 2 | CPU | RK3399 , hexa-core, main frequency 2.0GHz | | | | | |
| | RAM+ROM | Standard configuration4G+32G, optional with 4+64G; | | | | | |
| | Android system | Android 7.1/Android 10 | | | | | |
| Android option 3 | CPU | RK3566 , quad core, main frequency 1.8GHz | | | | | |
| | RAM+ROM | Standard configuration 2G+16G, optional with 4+32G; | | | | | |
| | Android system | Android 11 | | | | | |
| Android option 4 | CPU | RK3568 , quad-core, main frequency 2.0GHz | | | | | |
| | RAM+ROM | Standard configuration 2G+16G, optional with 4+32G; | | | | | |
| | Android system | Android 11 | | | | | |
| Android option 5 | CPU | 972T , quare core, main frequency 1.9GHz | | | | | |
| | RAM+ROM | Standard configuration 2G+16G, optional with 4+32G; | | | | | |
| | Android system | Android 9.0 | | | | | |
| Wireless | WIFI support | | | | | | |
| Bluetooth | 4.0 | | | | | | |
| Ethernet | 1,10M/100M self-adapting Ethernet | | | | | | |
| Ports | 2*USB,1*TF, 1*HDMI out, 1*LAN, 1*DC | | | | | | |

| Items | V032FDS02 | V043FDS02 | V049FDS02 | V055FDS02 | V065FDS02 | V075FDS02 | V086FDS02 |
|--------------------------------|--|----------------|----------------|----------------|----------------|-----------------|-------------------|
| PC system(optional) | | | | | | | |
| Processor (optional) | i3: i3-3110M/i3-3120M, dual core, frequency 2.4GHZ DDR3 i3-4000M,dual core, frequency 2.4GHZ DDR3 i3-6100U,dual core, frequency 2.3GHZ DDR3/DDR4 i5: i5-3210M/i5-3230M, dual core, frequency 2.5Ghz DDR3 I5-4200M,dual core, frequency 2.5Ghz DDR3 I5-6200U,dual core, frequency 2.5Ghz DDR3/DDR4 i7: i7-4600M,dual core, frequency 2.9Ghz DDR3 Any processor specs. can be customized | | | | | | |
| RAM (optional) | 4GB/8GB/16GB optional | | | | | | |
| Graphics | Intel UHD Graphics 600/630 | | | | | | |
| SSD/HDD (optional) | 128GB/256GB/512GB M.2 SATA SSD | | | | | | |
| USB ports | 6 | | | | | | |
| Ethernet port | 1*LAN RJ45(Gigabit) | | | | | | |
| Wireless | Wifi 802.11 a/b/g/n/ac 2.4GHz and 5GHz | | | | | | |
| Bluetooth | optional | | | | | | |
| Audio Ports | 1*3.5mm line out | | | | | | |
| Operation system | Windows 10 pro (trial version unlicensed) | | | | | | |
| Audio | | | | | | | |
| Speaker | 2*8 Ω 5W | | | | | | |
| Power Supply | | | | | | | |
| Voltage | AC 110V-240V, 50HZ/60HZ | | | | | | |
| Working power consumption | 80W | 118W | 180W | 190W | 240W | 330W | 390W |
| Standby power consumption | 0.5W | 0.5W | 0.5W | 0.5W | 0.5W | 0.5W | 0.5W |
| Environmental | | | | | | | |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) | | | | | | |
| Storage Temperature | -15°C to 55°C (-5°F to 131°F) | | | | | | |
| Operating Humidity | 20% to 80% non-condensing humidity | | | | | | |
| Storage Humidity | 20% to 90% non-condensing humidity | | | | | | |
| Physical specifications | | | | | | | |
| Panel Dimensions | 446*1700*158mm | 583*1785*158mm | 658*1855*158mm | 734*1905*158mm | 857*2055*158mm | 1005*2000*190mm | 1154*2100.1*190mm |
| Packed Dimensions | 1800*260*600m | 1880*260*750m | 1910*260*800m | 2000*260*890m | 2110*290*1000 | 2199*290*1125 | 2217*290*1275 |
| | m | m | m | m | mm | mm | mm |
| Net Weight | 80kg | 100kg | 113kg | 160kg | 190kg | 210kg | 240kg |
| Packed Weight | 90kg | 110kg | 130kg | 180kg | 210kg | 230kg | 260kg |
| Accessories | Power cable 1.5m*1,WIFI antenna*1, key*2, floor stand basement*1, screws*8, screw driver*1 | | | | | | |
| Certifications | CE FCC ROHS CB | | | | | | |
| Warranty | One year | | | | | | |